

ELAPRO SFB

TD331 Technical Data Sheet



Areas of application

ELAPRO SFB is used as a butt joint band for coverage under butt joints. For this purpose, it is laid centrally under a non-overlapping non-woven material joint to create smooth surfaces.

Characteristics

- Highly tear-resistant
- Flexible
- Non-slip finish
- Easy to process

Delivery form

50 m roll, width: 12.5 cm

Tools

Processing: Scissors

Compatible system components

- ELAPRO 1k-SIL
- ELAPRO 1k-CRYL
- ELAPRO Vlies 110 / 120

Processing

ELAPRO SFB is integrated centrally under the butt-jointed non-woven material joints in the wet base coat. Ensure that no cavities, wrinkles, bubbles etc. form. There must be at least 1.0 kg/m² of sealing material between the ELAPRO SFB and the ELAPRO Vlies. The non-woven material is rolled gently into the layer applied previously with a roller.

This type of butt joint overlap creation is only permitted with ELAPRO waterproofing products.

Material properties

System basis	Polyester
Weight	35 g/m ²
Temperature resistance	-30 to +70°C
Standard colour	White

Processing-relevant data

Consumption	1.0 m/lm
-------------	----------

The non-woven material must overlap by 5 cm on both sides of the SFB.

Storage and shelf life

Protect against soiling. Shelf life is virtually unlimited when stored dry, vertically and without kinks.

Disposal

Product residues: AVV 04 02 21

Packaging: AVV 15 01 02

Note: Product residues and packaging must be disposed of properly in compliance with the European List of Waste Materials (AVV/formerly EAK).

General information

All information provided here serves only to describe the material and is based on tests and results achieved in practical use. As a result, no liability can be accepted for its accuracy or completeness. Advice is provided to the best of our knowledge and does not release users from testing by accredited specialists such as planners and experts. Colour deviations or changes do not affect the products' technical parameters. The times specified are reduced at higher ambient and surface temperatures and extended at lower ambient and surface temperatures. All data is subject to changes without notice. The data sheet shall cease to be valid 5 years after publication. The latest version must always be used. It is available in the download area on our website www.elapro.de. The details and recommendations in this product information correspond to the current state of our knowledge and are provided to inform the buyer. They do not release the buyer from assessing the products for suitability and use on the respective substrate. The products described must only be processed as a system with the system components mentioned here. We guarantee flawless quality within the framework of our terms of delivery and payment.

Safety instructions

All safety instructions on the containers, the technical product information and the safety data sheets and relevant local, national and EU regulations must be complied with. Personal occupational health and safety must be observed.